•)) Direct Connect



MODEL 420

Collect, Exchange and Back-up On-site Data.

With DC-420, retail operators can securely access and exchange data to automatically collect and update pricing, sales and inventory information. Powered by an Intel® Celeron® processor, it seamlessly transfers LPA, foodservice, POS and automatic tank gauging (ATG) data to back-office and analytics systems.

KEY FEATURES

- Real-time Analytics
- Rapid Deployment (Plug-and-Play)
- Centralized Configuation and Management
- Continuous Monitoring and Remote Access
- Offline Processing and Self-Correcting





•)) Direct Connect

MODEL 420

DATA SHEET

Basic Information

CPU Onboard Intel Celeron J4105/N4100/J4125(DDR4)

TDP 10W

BIOS American Megatrends Inc.

Chipset Intel Gemini Lake

Memory 1 x SO-DIMM DDR4 Slot Support 4GB DDR4/LPDDR4 upto 2400 MT/s

OS Windows 7/Windows 8/Windows 10/Linux

Audio Intel High Definition Audio Controller

Network 2 x RTL8168/8111/8112 Gigabit Ethernet Controller 10/100Mbps/1000Mbps BaseT LAN

Video Intel® UHD Graphics 600

Storage

MSATA 1 x M-SATA3.0 slot for MSATA SSD, support 6Gb/s

M.2 1 x M.2 slot for M.2 NGFF SSD, support 6Gb/s(customized for bulk order only)

SATA 1 x SATA3.0 slot for SATA HDD or SSD, support 6Gb/s

Wi-Fi

Module 1 x mini PCIE-half port for Wi-Fi module

Input/Output Ports

Switch 1 x Power On/Off Switch

LED 2 x LED

USB 4 x USB3.0

Display 1 x VGA, 1 x HDMI

LAN 2 x RJ45 Giga LAN

COM 2 x RS232 COM

Power and Working Environment

Input DC100-240V AC/50-60Hz

Output DC 12V/5A

Operating Temperature -10/+60 °C, 14/+140 °F Storage Temperature -20/+85 °C, -4/+185 °F

Relative Humidity 10%~90% (non-condensing)

Product Dimension and Detail

Size 135*127*39 mm (44 mm with foot

pad), 5.31*5*1.54 inch

Weight Net 0.55 kg, Gross 1.2 kg (Net 1.21

lbs, Gross 2.65 lbs)

Shell Black color aluminum alloy

Cooling Mode Fanless

Functions Auto Power On, RTC, WOL, PXE



